



## INFORMAZIONI TECNICHE

Corpo e flangia di chiusura in pressofusione di alluminio verniciato e resistente alla corrosione. Protezione con trattamento di anodizzazione, fondo con polveri epossidiche e verniciatura poliester. Viti in acciaio inox A4. Nonio graduato in acciaio inox AISI 304 con doppio serraggio per un sicuro posizionamento. Valvola in Gore per impedire la formazione di condensa all'interno del prodotto.

## TECHNICAL INFORMATION


Die-cast aluminium body and locking ring. Protection with anodizing treatment, epoxy powder base coating and polyester painting. A4 stainless steel screws. AISI 304 stainless steel graduated ring to keep right adjustment. Gore valve to prevent condensation inside the product.

OVERVIEW




Nonio graduato per un corretto posizionamento del prodotto.

Vernier scale for the correct aiming of the product.




È possibile fissare il proiettore nel terreno attraverso l'utilizzo del picchetto in acciaio inox AISI 316L.

It is possible to fix the floodlight into the ground through an AISI 316L stainless steel spike.




È possibile applicare il prodotto su palo attraverso gli accessori dedicati.

It is possible to attach the product onto a pole by means of dedicated accessories.



È possibile applicare a tutte le versioni una tubo concentrante o una visiera antiabbagliamento.

It is possible to apply a narrow beam tube or a glare shield to all versions.



Il paletto prese 89 10 502.08 permette la connessione del prodotto alla rete.

The connecting column code 89 10 502.08 allows the connection of the product to power network.




**WHITE LED 230V**



SPOT





MEDIUM





WIDE





**84 24 111**  
**LED 3000K CRI>80**  
 4,5W / 565 lm Nominal data  
**5,9W / 470 lm Real data**  
 220-240V 0/50/60Hz  
**Surge protection included**  
 A / A+ / A++  
 Cable length 0,5 m (3 x 1 mm<sup>2</sup>)



**84 24 113**  
**LED 3000K CRI>80**  
 4,5W / 565 lm Nominal data  
**5,9W / 440 lm Real data**  
 220-240V 0/50/60Hz  
**Surge protection included**  
 A / A+ / A++  
 Cable length 0,5 m (3 x 1 mm<sup>2</sup>)



**84 24 118**  
**LED 3000K CRI>80**  
 4,5W / 565 lm Nominal data  
**5,9W / 410 lm Real data**  
 220-240V 0/50/60Hz  
**Surge protection included**  
 A / A+ / A++  
 Cable length 0,5 m (3 x 1 mm<sup>2</sup>)



**RGBW 4 LED max. 500mA**



WIDE



**83 24 108**  
**4 LED RGBW**  
 max. 5,8W LED power  
 max. 500mA \*  
 4 channels  
 A / A+ / A++  
 Cable length 1,5 m (10 x 0,32 mm<sup>2</sup>)

**PRODUCT INFORMATION**


IP65  
 IK 06  
 4 mm flat tempered extra clear glass

\* Power supply excluded to be ordered separately

**AVAILABLE COLOURS**

.06 grey  
 .09 bronze  
 Other colours on request

**TECHNICAL DATA**



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
 Available upon request without surcharge (for the code composition, please refer to page 9)

**HELP YOU**

**LED**  
 LED COLOURS  
 TEMPERATURE  
 4000K

Other LED colours available on request

**COLORS**  
**FINISHES**  
 .01 black  
 .02 white  
 .07 corten  
 .08 anthracite

**INFO**  
 Ulteriori versioni sono disponibili consultando [www.platek.eu](http://www.platek.eu)

More versions are available on [www.platek.eu](http://www.platek.eu)

**ACCESSORI** (per maggiori dettagli consultare pagina 321)  
**ACCESSORIES** (for further details please refer to page 321)

**FILTER**  
 page 338  
 89 18 780 - Ellipsoidale  
 89 18 785 - Sandblasted  
 89 18 787 - Deflector  
 89 18 786 - Honeycomb

**FIXING**  
 page 339  
 90 05 605 - Spike

**SHIELD**  
 page 344  
 89 05 010.01 - Visor  
 89 05 080.01 - Tube

**CONTROLLER**  
 RGB/RGBW  
 page 322  
 89 56 135 - 24 LED  
 89 56 110 - 48 LED  
 89 56 115 - 384 LED

**IP CONNECTOR IN LINE**  
 page 336  
 89 17 014 - 3 x 1,5 mm<sup>2</sup>

**IP CONNECTOR FOR THROUGH WIRING**  
 page 336  
 89 17 004 - 3 x 4 mm<sup>2</sup>




More details at: [platek.eu/MICROSPRING](http://platek.eu/MICROSPRING)

WHITE  
COB LED  
230V




SPOT

**88 14 511**  
**LED 3000K COB CRI>80**  
18W / 2340 lm Nominal data  
**19,2W / 1630 lm Real data**  
220-240V 0/50/60Hz  
**Surge protection included**  
A / A+ / A++  
Cable length 1 m (3 x 1 mm<sup>2</sup>)




10°  
11600  
cd/klm





MEDIUM

**88 14 513**  
**LED 3000K COB CRI>80**  
18W / 2340 lm Nominal data  
**19,2W / 1610 lm Real data**  
220-240V 0/50/60Hz  
**Surge protection included**  
A / A+ / A++  
Cable length 1 m (3 x 1 mm<sup>2</sup>)




25°  
2900  
cd/klm




WIDE

**88 14 518**  
**LED 3000K COB CRI>80**  
18W / 2340 lm Nominal data  
**19,2W / 1580 lm Real data**  
220-240V 0/50/60Hz  
**Surge protection included**  
A / A+ / A++  
Cable length 1 m (3 x 1 mm<sup>2</sup>)



75°  
620  
cd/klm




RGBW COB LED  
available  
on request

PRODUCT INFORMATION

IP65  
IK 06  
5 mm flat tempered  
extra clear glass

AVAILABLE COLOURS  
.06 grey  
.09 bronze  
Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED  
LED COLOURS  
TEMPERATURE  
4000K

Other LED colours  
available on request

COLORS  
FINISHES  
.01 black  
.02 white  
.07 corten  
.08 anthracite

INFO  
Ulteriori versioni sono  
disponibili consultando  
www.platek.eu

More versions are available on  
www.platek.eu

ACCESSORI (per maggiori dettagli consultare pagina 321)  
ACCESSORIES (for further details please refer to page 321)

FILTER  
page 338  
89 18 670 - Ellipsoidal  
89 18 675 - Sandblasted

FIXING  
page 339  
90 05 600 - Spike

SHIELD  
page 344  
89 05 015.01 - Visor  
89 05 085.01 - Tube

CONNECTION  
page 343  
89 51 040 - Ø 60 mm  
89 51 045 - Ø 102 mm  
89 51 050 - Ø 114 mm

IP CONNECTOR  
IN LINE  
page 336  
89 17 014 - 3 x 1,5 mm<sup>2</sup>

IP CONNECTOR FOR  
THROUGH WIRING  
page 336  
89 17 004 - 3 x 4 mm<sup>2</sup>





More details at:  
platek.eu/  
MINISPRING



WHITE LED 230V





**84 23 311**  
**LED 3000K CRI>80**  
 20,5W / 1980 lm Nominal data  
**21,7W / 1360 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 1 m (3 x 1 mm<sup>2</sup>)



**84 23 313**  
**LED 3000K CRI>80**  
 20,5W / 1980 lm Nominal data  
**21,7W / 1230 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 1 m (3 x 1 mm<sup>2</sup>)



**84 23 318**  
**LED 3000K CRI>80**  
 20,5W / 1980 lm Nominal data  
**21,7W / 1100 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 1 m (3 x 1 mm<sup>2</sup>)



RGBW 16 LED max. 350mA



**83 23 408**  
**16 LED RGBW**  
 max. 16,2W LED power  
 max. 350mA \*  
 4 channels + 1 channel NTC  
 A / A+ / A++  
 Cable length 1 m (10 x 0,32 mm<sup>2</sup>)

PRODUCT INFORMATION


IP65  
 IK 06  
 5 mm flat tempered extra clear glass

\* POWER SUPPLY EXCLUDED to be ordered separately

AVAILABLE COLOURS

.06 grey  
 .09 bronze  
 Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
 Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED LED COLOURS TEMPERATURE 4000K

Other LED colours available on request

OPTICS OPTIC ELLIPTICAL

COLORS FINISHES  
 .01 black  
 .02 white  
 .07 corten  
 .08 anthracite

INFO Ulteriori versioni sono disponibili consultando [www.platek.eu](http://www.platek.eu)

More versions are available on [www.platek.eu](http://www.platek.eu)

ACCESSORI (per maggiori dettagli consultare pagina 321)  
 ACCESSORIES (for further details please refer to page 321)

FILTER page 338  
 89 18 670 - Ellipsoidal  
 89 18 675 - Sandblasted

FIXING page 339  
 90 05 600 - Spike

SHIELD page 344  
 89 05 015.01 - Visor  
 89 05 085.01 - Tube

CONNECTION page 343  
 89 51 040 - Ø 60 mm  
 89 51 045 - Ø 102 mm  
 89 51 050 - Ø 114 mm

IP CONNECTOR IN LINE page 336  
 89 17 014 - 3 x 1,5 mm<sup>2</sup>

IP CONNECTOR FOR THROUGH WIRING page 336  
 89 17 004 - 3 x 4 mm<sup>2</sup>

RGB+W CONTROLLER RGB/RGBW page 322  
 89 56 135 - 24 LED  
 89 56 110 - 48 LED  
 89 56 115 - 384 LED



More details at: [platek.eu/MINISPRING](http://platek.eu/MINISPRING)

WHITE  
COB LED  
230V



SPOT





MEDIUM



RGBW COB LED  
available  
on request



**88 15 811**  
**LED 3000K COB CRI>80**  
37W / 5300 lm Nominal data  
**45,2 W / 4240 lm Real data**  
220-240V 50/60Hz  
**Surge protection included**  
A / A+ / A++  
Cable length 3 m (2 x 1 mm<sup>2</sup>)



**88 15 813**  
**LED 3000K COB CRI>80**  
37W / 5300 lm Nominal data  
**45,2 W / 3975 lm Real data**  
220-240V 50/60Hz  
**Surge protection included**  
A / A+ / A++  
Cable length 3 m (2 x 1 mm<sup>2</sup>)




PRODUCT INFORMATION

IP65  
IK 06  
5 mm flat tempered  
extra clear glass

AVAILABLE COLOURS

.06 grey  
.09 bronze  
Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED  
LED COLOURS  
TEMPERATURE  
4000K

Other LED colours  
available on request

COLORS  
FINISHES  
.01 black  
.02 white  
.07 corten  
.08 anthracite

INFO  
Ulteriori versioni sono  
disponibili consultando  
www.platek.eu

More versions are available on  
www.platek.eu

ACCESSORI (per maggiori dettagli consultare pagina 321)  
ACCESSORIES (for further details please refer to page 321)

FILTER  
page 338  
89 18 660 - Ellipsoidal  
89 18 665 - Sandblasted

FIXING  
page 339  
90 05 600 - Spike

SHIELD  
page 344  
89 05 020.01 - Visor  
89 05 090.01 - Tube

CONNECTION  
page 343  
89 51 040 - Ø 60 mm  
89 51 045 - Ø 102 mm  
89 51 050 - Ø 114 mm

IP CONNECTOR  
IN LINE  
page 336  
89 17 014 - 3 x 1,5 mm<sup>2</sup>

IP CONNECTOR FOR  
THROUGH WIRING  
page 336  
89 17 004 - 3 x 4 mm<sup>2</sup>

RGB  
+W  
CONTROLLER  
RGB/RGBW  
page 322  
89 56 135 - 24 LED  
89 56 110 - 48 LED  
89 56 115 - 384 LED





More details at:  
platek.eu/  
SPRING



WHITE LED 230V





**84 22 511**  
**LED 3000K CRI>80**  
 40,5W / 4680 lm Nominal data  
**44W / 3750 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 3 m (2 x 1 mm<sup>2</sup>)



**84 22 513**  
**LED 3000K CRI>80**  
 40,5W / 4680 lm Nominal data  
**44W / 3680 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 3 m (2 x 1 mm<sup>2</sup>)



**84 22 518**  
**LED 3000K CRI>80**  
 40,5W / 4680 lm Nominal data  
**44W / 3620 lm Real data**  
 220-240V 0/50/60Hz  
**Thermal LED protection**  
 A / A+ / A++  
 Cable length 3 m (2 x 1 mm<sup>2</sup>)



RGBW 24 LED max. 500mA



**83 22 508**  
**24 LED RGBW**  
 max. 34,8W LED power  
 max. 500mA \*  
 4 channels + 1 channel NTC  
 A / A+ / A++  
 Cable length 1,3 m (10 x 0,32 mm<sup>2</sup>)

PRODUCT INFORMATION


IP65  
 IK 06  
 5 mm flat tempered extra clear glass

\* POWER SUPPLY EXCLUDED to be ordered separately

AVAILABLE COLOURS

.06 grey  
 .09 bronze  
 Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
 Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

LED LED COLOURS TEMPERATURE 4000K

Other LED colours available on request

COLORS FINISHES  
 .01 black  
 .02 white  
 .07 corten  
 .08 anthracite

INFO  
 Ulteriori versioni sono disponibili consultando [www.platek.eu](http://www.platek.eu)

More versions are available on [www.platek.eu](http://www.platek.eu)

ACCESSORI (per maggiori dettagli consultare pagina 321)  
 ACCESSORIES (for further details please refer to page 321)

FILTER  
 page 338  
 89 18 660 - Ellipsoidale  
 89 18 665 - Sandblasted

FIXING  
 page 339  
 90 05 600 - Spike

SHIELD  
 page 344  
 89 05 020.01 - Visor  
 89 05 090.01 - Tube

CONNECTION  
 page 343  
 89 51 040 - Ø 60 mm  
 89 51 045 - Ø 102 mm  
 89 51 050 - Ø 114 mm

IP CONNECTOR IN LINE  
 page 336  
 89 17 014 - 3 x 1,5 mm<sup>2</sup>

IP CONNECTOR FOR THROUGH WIRING  
 page 336  
 89 17 004 - 3 x 4 mm<sup>2</sup>

RGB +W CONTROLLER RGB/RGBW  
 page 322  
 89 56 135 - 24 LED  
 89 56 110 - 48 LED  
 89 56 115 - 384 LED




More details at: [platek.eu/SPRING](http://platek.eu/SPRING)


METAL HALIDE LAMP




**88 15 631**  
**HIT-TC-CE 70W - G8,5**  
 70W / 6600 lm LAMP data  
**82W / 4290 lm Real data**  
 220-240V 0/50/60Hz  
 A / A+  
 Cable length 3 m (2 x 1 mm<sup>2</sup>)




2°  
 31422  
 cd/klm



**88 15 632**  
**HIT-TC-CE 70W - G8,5**  
 70W / 6600 lm LAMP data  
**82W / 3960 lm Real data**  
 220-240V 0/50/60Hz  
 A / A+  
 Cable length 3 m (2 x 1 mm<sup>2</sup>)



22°  
 2616  
 cd/klm




PRODUCT INFORMATION

IP65  
 IK 06  
 5 mm flat tempered  
 extra clear glass

AVAILABLE COLOURS

■ .06 grey  
 ■ .09 bronze  
 Other colours on request

TECHNICAL DATA



Disponibile su richiesta senza maggiorazione di prezzo (per la composizione del codice consultare pagina 8)  
 Available upon request without surcharge (for the code composition, please refer to page 9)

HELP YOU

COLORS	FINISHES
	■ .01 black
	■ .02 white
	■ .07 corten
	■ .08 anthracite

INFO  
 Ulteriori versioni sono  
 disponibili consultando  
[www.platek.eu](http://www.platek.eu)

More versions are available on  
[www.platek.eu](http://www.platek.eu)

ACCESSORI (per maggiori dettagli consultare pagina 321)  
 ACCESSORIES (for further details please refer to page 321)

**FILTER**  
 page 338  
 89 18 660 - Ellipsoidale  
 89 18 665 - Sandblasted

**FIXING**  
 page 339  
 90 05 600 - Spike

**SHIELD**  
 page 344  
 89 05 020.01 - Visor  
 89 05 090.01 - Tube

**CONNECTION**  
 page 343  
 89 51 040 - Ø 60 mm  
 89 51 045 - Ø 102 mm  
 89 51 050 - Ø 114 mm

**IP CONNECTOR  
 IN LINE**  
 page 336  
 89 17 014 - 3 x 1,5 mm<sup>2</sup>

**IP CONNECTOR FOR  
 THROUGH WIRING**  
 page 336  
 89 17 004 - 3 x 4 mm<sup>2</sup>



More details at:  
[platek.eu/SPRING](http://platek.eu/SPRING)