


ANTLIA LED

Downlights




Description:	Surface mounted LED downlight Light distribution type: direct Optical system: faceted aluminium reflector, 40°, low glare Housing: aluminum Colour: white (RAL9016)
General data:	Mains voltage: 220-240V, 50-60Hz LED lifetime, h: 50000/L80B50 (75000/L80B50 low power versions) SDCM: 3 Protection class IEC: I Ingress protection code: IP20 Mechanical impact resistance: IK02 Operating temperature range, °C: ta 0...+35
Installation:	On the ceiling. Push-in terminal, 3x2x2.5mm2
Environment:	Indoor
Application:	Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Antlia LED1x1600 D342 T830	168	168	172	1549	14,1	110	80+	3000	1,00
Antlia LED1x2300 D343 T830	168	168	172	2150	20,7	104	80+	3000	1,00
Antlia LED1x3000 D344 T830	168	168	172	2900	28,4	102	80+	3000	1,00
Antlia LED1x1600 D342 T840	168	168	172	1597	14,1	113	80+	4000	1,00
Antlia LED1x2300 D343 T840	168	168	172	2216	20,7	107	80+	4000	1,00
Antlia LED1x3000 D344 T840	168	168	172	2990	28,4	105	80+	4000	1,00

*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Available options:

DALI	Driver with DALI interface and switch-control dimming
1G	Strain relief for power supply cable
SUS	Suspended version
RAL	RAL colour
T830	Colour temperature 3000K, CRI 80+
T840	Colour temperature 4000K, CRI 80+



Available accessories:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
*note - 1pcs MTG KIT SUSI for one fitting required