


# AURIGA C LED

## Downlights



<b>Description:</b>	Recessed mounted LED downlight Light distribution type: direct Optical system: clear glass diffuser, faceted aluminium reflector, 40°, UGR≤19/ opal PMMA diffuser/ translucent micro-prismatic PMMA diffuser Housing: aluminium Colour: white (RAL9016)
<b>General data:</b>	Mains voltage: 220-240V, 0/50/60Hz LED lifetime, h: 75000/L80B50 SDCM: 3 Protection class IEC: II Ingress protection code: IP44 Mechanical impact resistance: IK05 Operating temperature range, °C: ta 0...+35
<b>Installation:</b>	In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm2
<b>Environment:</b>	Indoor
<b>Application:</b>	Office, education, hotel, corridor, bathroom, retail, showroom, exhibition, public place

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Auriga C LED1x1600 D336 T830 CLR	195	195	140	1549	14,1	110	80+	3000	0,80
Auriga C LED1x2300 D337 T830 CLR	195	195	140	2150	19,6	110	80+	3000	0,80
Auriga C LED1x3000 D338 T830 CLR	195	195	140	2900	28,1	103	80+	3000	0,80
Auriga C LED1x1600 D336 T840 CLR	195	195	140	1597	14,1	113	80+	4000	0,80
Auriga C LED1x2300 D337 T840 CLR	195	195	140	2216	19,6	113	80+	4000	0,80
Auriga C LED1x3000 D338 T840 CLR	195	195	140	2990	28,1	106	80+	4000	0,80
Auriga C LED1x1600 D336 T830 OP LT80	195	195	140	1417	14,1	100	80+	3000	0,80
Auriga C LED1x2300 D337 T830 OP LT80	195	195	140	1967	19,6	101	80+	3000	0,80
Auriga C LED1x3000 D338 T830 OP LT80	195	195	140	2653	28,1	94	80+	3000	0,80
Auriga C LED1x1600 D336 T840 OP LT80	195	195	140	1461	14,1	103	80+	4000	0,80
Auriga C LED1x2300 D337 T840 OP LT80	195	195	140	2027	19,6	104	80+	4000	0,80
Auriga C LED1x3000 D338 T840 OP LT80	195	195	140	2735	28,1	97	80+	4000	0,80
Auriga C LED1x1600 D336 T830 MPRZ LT92	195	195	140	1398	14,1	99	80+	3000	0,80
Auriga C LED1x2300 D337 T830 MPRZ LT92	195	195	140	1940	19,6	99	80+	3000	0,80
Auriga C LED1x3000 D338 T830 MPRZ LT92	195	195	140	2617	28,1	93	80+	3000	0,80
Auriga C LED1x1600 D336 T840 MPRZ LT92	195	195	140	1442	14,1	102	80+	4000	0,80
Auriga C LED1x2300 D337 T840 MPRZ LT92	195	195	140	1999	19,6	102	80+	4000	0,80
Auriga C LED1x3000 D338 T840 MPRZ LT92	195	195	140	2698	28,1	96	80+	4000	0,80

\*Tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C. NORTHCLIFFE LIGHTING is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

**Available options:**

DALI	Driver with DALI interface	Europlug-1.5m	2-pole "Europlug" type plug with 2x1.0mm <sup>2</sup> 1.5m cable
EM3	Emergency version 3 hours	Europlug-3.0m	2-pole "Europlug" type plug with 2x1.0mm <sup>2</sup> 3.0m cable
EM3B	Emergency version 3 hours (best available technology)	OP LT80	Opal diffuser with high light transmittance
EM3A	Emergency version equipped with an autonomous testing system, 3 hours	MPRZ LT92	Translucent micro-prismatic diffuser with high light transmittance
EM3D	Emergency version 3 hours with DALI interface	RAL	RAL colour
WIE3-0.5m	3-pole "Wieland - gesis classic" type or compatible connector with 0.5m cable	T830	Colour temperature 3000K, CRI 80+
WIE5D-0.5m	5-pole DALI "Wieland - gesis classic" type or compatible connector with 0.5m cable	T840	Colour temperature 4000K, CRI 80+
		T930	Colour temperature 3000K, CRI 90+
		T940	Colour temperature 4000K, CRI 90+

