


CYGNI LED

Product Group: Outdoor accent lighting



Images for the product family and options:



Description: An architectural LED wall washer with symmetrical light distribution used for indoor and outdoor accent lighting applications
 Optics: 30° light beam
 Diffuser: tempered glass, impact resistant
 Body: extruded aluminum, light grey finish, silicone rubber sealing and brass cable gland provides reliable protection

General data: Mains voltage: 220-240V, 50-60Hz
 Power factor: >0,95
 Light source: LED
 Light source included: Yes
 Light distribution type: Direct
 LED lifetime, h: 50000/L80B50
 Operating temperature range, °C: ta -25...+40
 Protection class IEC: I
 Ingress protection code: IP66
 Mechanical impact resistance: IK09
 EEC: A++

Installation: Surface mounted luminaire is designed to be fixed to walls of any type. Cable, 1.0m, 3x0.75mm2

Environment: Outdoor


Application: Facade illumination

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Cygni LED1x1900 D775 T740 L30	705	82	164	1897	15,8	120	80+	4000	3,00
Cygni LED1x2400 D776 T740 L30	705	82	164	2370	22,6	105	80+	4000	3,00
Cygni LED1x3200 D777 T740 L30	705	82	164	3162	29,9	106	80+	4000	3,00
Cygni LED1x3800 D778 T740 L30	1265	82	164	3794	29,9	127	80+	4000	6,00
Cygni LED1x4800 D779 T740 L30	1265	82	164	4740	42,7	111	80+	4000	6,00
Cygni LED1x6400 D780 T740 L30	1265	82	164	6324	59,7	106	80+	4000	6,00

* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

Available options:

DALI Driver with DALI interface
 L30 Optics with 30x30° beam angle
 T730 Colour temperature 3000K, CRI 70+
 T740 Colour temperature 4000K, CRI 70+



Available accessories:



Product: Power supply connector - IP66/IP68, 3x1.5mm2

Description: Quick and easy to connect power supply and luminaire cables connector - IP66/IP68, 3x1.5mm2, 400V/16A, 1pcs